

SELF-LOCKING SOLID FLOORING MAXI MOSAICO

580,5x195



INTENDED USE

Pavement of outdoor driveway and pedestrian areas.

CHAPTER ENTRY

Solid flooring, **Maxi Mosaico** type, of a total size of mm. 580.5 x 195.0 made of compressed vibro concrete with low porosity inerti, controlled particle size and high mechanical strength guaranteed by the compression vibro processing of a value not less than $56 \div 60 \text{ N/mm}^2$. Compliant with UNI EN 1338.

USES

The **Maxi Mosaico**, consists of three elements, two rectangular and one square, which can be inserted in other quadrangular modules. This artifact is suitable for creating closing bands, creating graphic lines, delimiting paths or composing particular graphic effects. It is suitable for paving pedestrian areas, boulevards, squares, public parks inserted in the urban fabric. Due to its particular construction characteristics, due to the poor absorption of water, it is particularly suitable in areas with frost problems.

TECHNICAL INFORMATION

PRODUCT SIZE (mm)	Width 195.0 - Length 260.0/195.0/130.0
THICKNESS (mm)	60.0
COLORING	Inorganic Oxides
PACKAGING	Wood Pallets
PALLETS WEIGHT (KG)	1330
QUANTITY OF PALLET (PIECES x MQ)	25.0
SQUARE METERS PER PALLET	10.0
THICKNESS TOLERANCES	$\pm 2 \text{ mm (a)}$
AVERAGE VOLUME MASS	$> 2.200 \text{ Kg/dm}^3 \text{ (a)}$
AVERAGE COMPRESSIVE STRENGTH	$> 50 \div 60 \text{ N/mm}^2 \text{ (a)}$
FROST RESISTANCE	Non Frosty (b)
AVERAGE WATER ABSORPTION	$< 12 \% \text{ (b)}$
RESISTANCE TO ABRASION	Class 2 (b)

MATERIAL CHARACTERISTICS

Compressed vibro concrete monolayer
(for non-colored: white and gray)

Double layer in compressed vibro concrete
(for colors: dark and light)

REFERENCE REGULATIONS

UNI 9065 (replaced by UNI EN 1338)

UNI EN 1338 Appendices C to G

Regio Decreto N. 2234 of 16/11/39