

SELF-LOCKING SOLID FLOORING MOSAICO

126x189



INTENDED USE

Paving of external driveways and pedestrian areas.

CHAPTER ENTRY

Solid flooring, **Mosaico** type, mm in size. 126.0 x 189.0 made of compressed vibro concrete with low porosity inert, controlled particle size and high mechanical strength guaranteed by vibro compression processing of a value not less than $56 \div 60 \text{ N/mm}^2$. Compliant with UNI EN 1338.

USES

The **Mosaico**, consists of three basic elements of different sizes. The area of use is very large, although it is suggested for paving alleys and squares of the historic centers. Its use is also indicated in residential buildings in ancient style and in buildings where you want to highlight the charm of the ancient. Due to its particular construction characteristics, due to the poor absorption of water, it is particularly suitable in areas with frost problems.

TECHNICAL INFORMATION

PRODUCT SIZE (mm)	Width 126.0 - Length 189.0
THICKNESS (mm)	60.0
COLORING	Inorganic Oxides
PACKAGING	Wood Pallets
PALLETS WEIGHT (KG)	1150
QUANTITY OF PALLET (PIECES x MQ)	42.5
SQUARE METERS PER PALLET	8.4
THICKNESS TOLERANCES	$\pm 2 \text{ mm}$ (a)
AVERAGE VOLUME MASS	$> 2.200 \text{ Kg/dm}^3$ (a)
AVERAGE COMPRESSIVE STRENGTH	$> 50 \div 60 \text{ N/mm}^2$ (a)
FROST RESISTANCE	Non Frosty (b)
AVERAGE WATER ABSORPTION	$< 12 \%$ (b)
RESISTANCE TO ABRASION	Class 2 (b)

MATERIAL CHARACTERISTICS

Compressed vibro concrete monolayer
(for non-colored: white and gray)

Double layer in compressed vibro concrete
(for colors: dark and light)

REFERENCE REGULATIONS

UNI 9065 (replaced by UNI EN 1338)

UNI EN 1338 Appendices C to G

Regio Decreto N. 2234 of 16/11/39