

SELF-LOCKING SOLID FLOORING QUADRELLO

100x100



INTENDED USE

Pavement of outdoor driveway and pedestrian areas.

CHAPTER ENTRY

Solid flooring, **Quadrello** type, mm in size. 100.0 x 100.0 made of compressed vibro concrete with low porosity inerti, controlled particle size and high mechanical strength guaranteed by vibro compression processing of a value not less than $56 \div 60$ N/mm². Compliant with UNI EN 1338.

USES

The artifact, type **Quadrello**, is a square element of modular dimensions; it can be used either alone or combined with other modules. Such an artifact can be used to dab the edges of flooring, carried out with other models. It adapts to the flooring of small areas, such as sidewalks and courtyards. Due to its particular construction characteristics, due to the poor absorption of water, it is particularly suitable in areas with ice problems.

TECHNICAL INFORMATION

PRODUCT SIZE (mm)	Width 100.0 - Length 100.0
THICKNESS (mm)	60.0
COLORING	Inorganic Oxides
PACKAGING	Wood Pallets
PALLETS WEIGHT (KG)	1080
QUANTITY OF PALLET (PIECES x MQ)	100.0
SQUARE METERS PER PALLET	8.10
THICKNESS TOLERANCES	± 2 mm (a)
AVERAGE VOLUME MASS	> 2.200 Kg/dm ³ (a)
AVERAGE COMPRESSIVE STRENGTH	> 50 ÷ 60 N/mm ² (a)
FROST RESISTANCE	Non Frosty (b)
AVERAGE WATER ABSORPTION	<12 % (b)
RESISTANCE TO ABRASION	Class 2 (b)

REFERENCE REGULATIONS

UNI 9065 (replaced by UNI EN 1338)

UNI EN 1338 Appendices C to G

Regio Decreto N. 2234 of 16/11/39