

# SELF-LOCKING SOLID FLOORING VENTAGLIO

## 212x108



### INTENDED USE

Paving of external driveways and pedestrian areas.

### CHAPTER ENTRY

Solid flooring, **Ventaglio** type, mm in size. 212.0 x 108.0 made of compressed vibro concrete with low porosity inerti, controlled particle size and high mechanical strength guaranteed by vibro compression processing of a value not less than  $56 \div 60$  N/mm<sup>2</sup>. Compliant with UNI EN 1338.

### USES

The artifact, type **Ventaglio**, given its shape lends itself well to the flooring of parks; its rounded geometry allows a quick and perfect installation. This type of solid in light coloring guarantees an excellent architectural result and thanks to its particular construction characteristics, given the poor absorption of water, it is particularly suitable in areas with frost problems.

## TECHNICAL INFORMATION

PRODUCT SIZE (mm)	Width 212.0 - Length 108.0
THICKNESS (mm)	60.0
COLORING	Inorganic Oxides
PACKAGING	Wood Pallets
PALLETS WEIGHT (KG)	960
QUANTITY OF PALLET (PIECES x MQ)	34.3
THICKNESS TOLERANCES	± 2 mm (a)
AVERAGE VOLUME MASS	> 2.200 Kg/dm <sup>3</sup> (a)
AVERAGE COMPRESSIVE STRENGTH	> 50 ÷ 60 N/mm <sup>2</sup> (a)
FROST RESISTANCE	Non Frosty (b)
AVERAGE WATER ABSORPTION	<12 % (b)
RESISTANCE TO ABRASION	Class 2 (b)

## MATERIAL CHARACTERISTICS

Double Layer compressed vibro concrete

## REFERENCE REGULATIONS

UNI 9065 (replaced by UNI EN 1338)

UNI EN 1338 Appendices C to G